Applicant: STIELER, Ulrich
U.S. National Phase of PCT /EP 00/02258

REMARKS

By way of this Preliminary Amendment, the English translation of the Specification has been amended to conform to U.S. Practice. A Substitute Specification excluding claims under 37 C.F.R. 1.125(b) is submitted herewith accompanied by a marked-up copy of the specification showing the matter being added to and the matter being deleted from the specification of record. The Substitute Specification does not include new matter.

In addition, by the present amendment, claims 1-22 have been amended to conform to U.S. Practice. These amendments are not considered to narrow the scope of the claims. Claims 23 and 24 have been added, and are directed to alternative elements of original claims 3 and 22.

The Applicant respectfully submit that no new matter has been added by this Preliminary Amendment, and respectfully requests entry of this preliminary amendment.

CONCLUSION

In view of the foregoing amendments and remarks, the Applicant respectfully submits that the pending claims in the above-identified application are in condition for allowance, and a notice to that effect is earnestly solicited.

If the present application is found by the Examiner not to be in condition for allowance, then the Applicant hereby requests a telephone or personal interview to facilitate the resolution of any remaining matters. Applicant's attorney may be contact by telephone at the number indicated below to schedule such an interview.

Applicant: STIELER, Ulrich
U.S. National Phase of PCT /EP 00/02258

The Patent and Trademark Office is authorized to charge any additional fees incurred as a result of the filing hereof or credit any overpayment to our Deposit Account No. 19-0120.

Respectfully submitted,
STIELER, Ulrich, Applicant

By: ______________________
Michele J. Young, Reg. No. 43,299
Applicant's Attorney
SALTER & MICHAELSON
321 South Main Street
Providence, RI 02903
Tel: (401) 421-3141
Fax: (401) 861-1953
Customer No.: 000987

Dated: September 17, 2001

Applicant: STIELER, Ulrich
U.S. National Phase of PCT /EP 00/02258

Version with marking to show changes made:

1. (Amended Once) A [P]process for the production of physically foamed injection [moulded] molded articles, wherein in a first stage a propellant-free first melt portion [(6)] is fed into a cavity [(1)] (initial filling), in a second stage a physical propellant is added at elevated pressure to the following melt portion (propellant injection phase), and possibly in a third stage a propellant-free further melt portion is charged into the cavity [(1)], the production of the injection [moulded] molded articles occurring in the cavity,

[characterised in that] wherein metering of the physical propellant in the second stage occurs in a pressure regulated manner, wherein the pressure which is exerted on the propellant during the propellant injection phase is greater than the pressure which is exerted on the propellant in the phases between or before or after metered addition, and the expansion of the propellant occurs in the cavity [(1)].

2. (Amended Once) The [P]process [according to] of Claim 1, [characterised in that] wherein the propellant is a compressible fluid.

3. (Amended Once) The [P]process [according to] of Claim 1 [or 2, characterised in that] further comprising the step of maintaining the propellant [is kept] under pressure in the intermediate cycle times before and after the propellant injection phase[, or is present in a compressed state].

4. (Amended Once) The [P]process [according to] of Claim 3, [characterised in that in] further comprising maintaining the propellant at a pressure of at least p (crit) at a given temperature during the intermediate cycle times [the propellant is held a pressure of at least p (crit) of the propellant at the given temperature].

5. (Amended Once) The [P]process [according to one of the preceding claims] of Claim 1, [characterised in that] further comprising the step of controlling the pressure exerted on the propellant [is controlled] via a pressure control valve [(10)].

6. (Amended Once) The [P]process [according to] of Claim 5, [characterised in that] wherein the pressure control valve [(10)] is a multi-way valve.

7. (Amended Once) The [P]process [according to] of Claim 6, [characterised in that] wherein the multi-way valve is a 3/3-way proportional valve or a 2/3-way proportional valve [is used as multi-way valve].

8. (Amended Once) The [P]process [according to one of the preceding claims, characterised in that] of claim 1 further comprising the step of controlling the pressure [control in the case] of the critical propellants [additionally occurs] via at least one pressure relief valve [(4) which is] connected downstream of the pressure control valve [(10)].

9. (Amended Once) The [P]process [according to] of Claim 8, [characterised in that] wherein [the holding pressure of] at least one of the pressure relief valves [(4) is] has a holding pressure equal to or higher than the pressure at which a critical propellant is held in the intermediate cycle times.

10. (Amended Once) The [P]process according to [one of the preceding claims, characterised in that] Claim 1 further comprising the step of regulating the pressure preset by the pressure control valve [(10) is regulated] via one or more pressure relief valves [(4)] to the injection pressure at which the propellant is added to the melt via an injection point [(5)].

11. (Amended Once) The [P]process [according to one of the preceding claims, characterised in that] of claim 1, wherein the injection point [(5)] is configured as a throttle means.

12. (Amended Once) The [P]process [according to] of Claim 11, [characterised in that] wherein the injection point [(5)] is in the form of a defined gap in an injector or of an injector with a sinter metal.

13. (Amended Once) The [P]process [according to one of Claims 11 or 12, characterised in that] of Claim 11, wherein the injection point [(5)] is configured as a controlled closure mechanism.

14. (Amended Once) The [P]process [according to] of Claim 1[or one of the preceding Claims 3 to 13, characterised in that] further comprising the step of using water [is used] as the propellant.

15. (Amended Once) The [P]process [according to one of the preceding Claims 1 to 13, characterised in that] of Claim 1 further comprising the step of using a gas or gas mixture [is used] as the propellant.

16. (Amended Once) The [P]process [according to] of Claim[s] 15, [characterised in that] further comprising the step of using carbon dioxide [is used] as the propellant.

17. (Amended Once) The [P]process [according to] of Claim[s] 16, [characterised in that] wherein the carbon dioxide is held in the intermediate cycle times at a pressure of at least 60 bar [(= p (crit) CO_2 at room temperature)].

18. (Amended Once) The [P]process [according to one of the preceding claims, characterised in that for] of Claim 1 [the propellant injection phase] further comprising the step of elevating the

pressure of the propellant [is brought] during the propellant injection phase to a pressure of over 60 bar [via] using the pressure control valve [(10)].

19. (Amended Once) The [P]process [according to one of the preceding claims, characterised in that] of Claim 1 further comprising the step of generating a counterpressure [is generated] in the cavity [(1)].

20. (Amended Once) The [P]process [according to one of the preceding claims, characterised in that] of Claim1, wherein the physically foamed injection [moulded] molded article is selected from the group consisting of a handle, a knob, a gearshift knob, a steering wheel casing, a ball, a sphere, a fender, a float and a closing means for bottle-like containers.

21. (Amended Once) A [D]device for the metered addition of physical propellants to a foamable melt, [wherein the device comprises] comprising:

a storage means [(11)], in which the propellant is stored under pressure,

a pressure control valve [(10)] for regulating the propellant pressure, and

an injection point [(5)], which is configured as a throttle means, at which the propellant under pressure is fed to the melt, [characterised in that]

wherein a controlled closure mechanism is provided at the injection point [(5)].

22. (Amended Once) The [D]device [for the metered addition of physical propellants according to] of Claim 21, [characterised in that instead of the controlled closure mechanism or in addition to the controlled closure mechanism,] further comprising at least one pressure relief valve [(4) is provided].

Marked-up Copy of Substitute specification

~~Process for the Production of Physically Foamed Injection Moulded Articles~~

~~The present invention~~

PROCESS FOR THE PRODUCTION OF PHYSICALLY FOAMED INJECTION MOLDED ARTICLES

BACKGROUND

Technical Field

The present disclosure relates to a process for the production of physically foamed injection mo~~u~~lded articles and, in particular, to a process for the production of physically foamed injection mo~~u~~lded articles with an internal foam structure and a compact closed-pore external skin of the same material as the base body.

Related Art

The production of foamed plastics, for example, is achieved with the aid of so-called propellants, which expand a plastic, generally thermally softened plastic mass in the desired manner. In this case, the propellants are either generated in situ via chemical reaction of the components (chemical propellants), or compressed fluids, e.g. N_2, CO_2, are added under pressure to the starting material, in which case a foaming process of the plastic mass caused by the propellant is initiated upon the subsequent drop in pressure of the component mixture to normal pressure.

However, chemical propellants have a series of disadvantages. For instance, for use in foam injection mo~~u~~lding higher temperatures than are actually necessary for softening starting materials may have to be selected in order to reach the ignition point of the propellants, since the temperature at which the reaction of the components generating propellant starts is generally very high. Because of the high temperatures a higher expenditure of energy is necessary during melting of the raw materials. In addition, the cycle or cooling times are increased and a higher cooling power of the

cooling plants is necessary. In some circumstances, damage to the raw materials may also occur as a result of the comparatively high temperatures.

Chemical propellants which have not been converted can locate on the surface of the articles obtained and cause yellowing of the articles. Allergic skin reactions may also result upon contact with these articles.

Foam articles which have been obtained by means of chemical propellants are not recyclable, or if so only conditionally, since there is the risk that non-ignited propellants can lead to uncontrolled reactions during reuse.

Therefore, physical propellants are preferably used to foam plastics. Physical propellants allow optimum adaptation of the melting temperature to the respectively selected raw material, as a result of which the energy expenditure is reduced, optimum cycle and cooling times are made possible and, in addition, there is no risk that the raw materials could be detrimentally affected as a result of temperatures which are too high. Moreover, inexpensive gases such as CO_2, for example, can be used as physical propellants.

Physical propellants do not remain in the finished foam articles, but diffuse out within a comparatively short time. Therefore, these articles are fully recyclable, since there is no need to fear that propellant residues could lead to uncontrolled reactions.

Various processes are known for the production of articles from foamed plastic with a compact closed external skin and a cellular core cohering with the external skin or edge zone, also referred to as integral foam or structural foam.

For example, in the reaction injection mo~~u~~lding process (RIM), two reactive components are mixed together which harden and foam in the cavity of a mo~~u~~ld under reaction. Because of the quicker cooling at the wall of the mo~~u~~ld, the reaction mass solidifies more quickly there than in the interior of the ~~mould,~~mold and, as a result, the foaming process ceases earlier there than in the mo~~u~~ld interior, and a compact sealed external layer is formed.

As determined by the process, the reactive component mixture must be comparatively liquid in order to guarantee complete filling of the mo~~u~~ld before the reaction starts. However, this leads to irregularities on the surface of the formed article as a result of spray over and skin formation, which necessitates expensive finishing for high-grade articles, for which a perfect surface is required.

Moreover, for the RIM process the mo~~u~~ld must be treated with a separating agent prior to injection, which on the one hand requires more expenditure in processing and can additionally lead to residues on the finished article which must be removed. The relatively long cycle times are also disadvantageous.

~~Since~~

Because foaming in the RIM process is generally conducted chemically, the articles to be obtained are only conditionally recyclable.

Integral foams made of polyurethane to be used as working material primarily in the automobile industry, e.g. for steering wheel casings or gearshift knobs etc., are preferably produced using the RIM process. However, for this field of application the

articles must not only have as perfect a surface as possible, but also have pleasant skin feel (tactility).

It has been shown that articles of polyurethane integral foam have only a conditionally acceptable tactility.

It is also known to produce integral foams from thermoplastic urethane or thermoplastic elastomer by means of conventional injection moulding processes. Both chemical and physical propellants can be used in this case. Contrary to the RIM process, which requires special plants, already existing injection moulding plants without expensive refitting can be used for this.

The necessary finishing of the articles obtained is only slight.

DE 196 46 665 A1 describes a process for metering physical propellants, wherein a propellant is added at high pressure to the softened plastic material transported in the consumer, e.g. an extruder or an RIM machine, and the amount of propellant is regulated with a pressure control valve, which keeps the pressure difference constant via a rigid throttle means by regulating the pressure difference in dependence on the flow of propellant. The extrusion processes described here are continuous processes in which the propellant is permanently added.

A process for the production of multilayered articles with a foamed core and a non-expanded thermoplastic external skin is known from DE 1 778 457, wherein a first propellant-free melt and a second melt containing propellant as well as possibly a third propellant-free melt are firstly prepared and injected one after the other into an

appropriate mo~~u~~ld, in which case the mo~~u~~ld must be maintained at a temperature equal to or higher than the activation temperature of the propellant.

Where physical propellants are used, it is suggested that either the selected temperature of the melt upon leaving the nozzle is so high that, when a mo~~u~~ld with constant internal volume is used, the gas formation, and thus the expansion, still occurs below the pressure exerted on the substance in the mo~~u~~ld, and when a mo~~u~~ld with extendable interior is used, the gas formation, and thus the expansion, occurs by relieving the pressure exerted on the mo~~u~~ld interior to expand the mo~~u~~ld. There is no mention of the propellant being added directly to the melt flow which flows into the mo~~u~~ld, nor of the quantity of propellant apportioned to the melt flow being regulated via the pressure.

An improved process of the aforementioned type is specified in DE 1 948 454, wherein the propellant is injected into the melt flow shortly before entry into the mo~~u~~ld and the injection period is continued until the mixture quantity required to form the core has been inserted into the mo~~u~~ld. Solvents with a boiling point preferably between 20 and 150°C are specified as propellants, which are to prevent premature expansion under a corresponding pressure. There is likewise no mention here of a pressure regulation of the added quantity of propellant to the melt.

A process for the production of injection mo~~u~~lded articles with foamed core is described in ~~the US p~~U.S. Patent No. 4,548,776, according to which gaseous of gas-generated chemical propellant is already added to the melt in the extruder, is thoroughly mixed with this and the already foamed melt is then injected into the mo~~u~~ld.

In this case, the addition of propellant occurs via a porous insert at the injection point, a supply valve being provided in the feed pipe. This supply valve can be connected to an automatic control device, via which the pressure of the propellant to be fed is adjusted.

The object of the present ~~invention~~disclosure is to provide a process for the production of physically foamed injection mo~~u~~lded articles, with which injection mo~~u~~lded articles with an integral structure, excellent surface characteristics, ~~thus rendering expensive finishing unnecessary,~~ and ~~additionally~~ excellent tactility, can be obtained in a simple manner using conventional injection mo~~u~~lding plants, thus rendering expensive finishing unnecessary.

SUMMARY

The articles produced according to the ~~invention~~disclosure are suitable in particular for fields of application which set high quality requirements for surface structure and for which a pleasant sensory feel is of advantage on skin contact. The automobile industry is given as an example, for which handles, knobs such as gearshift knobs, steering wheel casings etc. of the foamed plastics obtained according to the ~~invention~~disclosure can be used. However, the process according to the ~~invention~~disclosure is in no way restricted to the production of articles for the automobile industry, but is quite generally suitable for the production of any desired foamed injection mo~~u~~lded articles.

For example, mass-produced articles such as closing means for bottle-like containers, e.g. stoppers or corks, may also be advantageously obtained according to this process. Further examples are balls, spheres, fenders, floats, etc.

A further field of use is the production of supporting parts, for example, for the aviation or automobile industry, in particular for parts where strength is relevant.

This object is achieved according to the ~~invention~~disclosure by a process for the production of physically foamed injection mo~~u~~lded articles, wherein firstly in a first stage a propellant-free first melt portion is fed into a cavity (initial filling), in a second stage a physical propellant is added at elevated pressure to the following melt portion (propellant injection phase), wherein metering of the physical propellant occurs at least in a pressure regulated manner, wherein the pressure which is exerted on the propellant during the propellant injection phase is greater than the pressure which is exerted on the propellant in the phases between or before or after metered addition, and the expansion of the propellant occurs in the cavity, and possibly in a third stage a propellant-free further melt portion is charged into the cavity.

This process also permits the formation of physically foamed injection mo~~u~~lded articles, the foamed core of which is completely or partially enclosed by a compact closed external skin, which has been produced without the addition of propellants, the core and the external skin being made of the same material.

The present ~~invention~~disclosure additionally relates to a device for the metered addition of propellants under elevated pressure to an expandable melt.

This device can also be advantageously used for the metered addition of compressible propellants.

The propellant-free melt portion firstly fed into the cavity in the first stage forms a compact closed external skin without pores in the finished foamed injection mo~~u~~lded articles.

Any desired fluid which expands upon corresponding pressure relief and foams the melt material in a suitable manner can be used as propellant. Hence, compressible fluids such as gases in liquid or supercritical phase, for example, may be used.

The use of carbon dioxide is recommended because of its ready availability.

A further preferred propellant is water.

The starting material for the melt is not subject to any special restrictions. Any desired thermoplastic melt material which is suitable for injection mo~~u~~lding and can be foamed may be used.

Examples are thermoplastic materials, but also further thermoplastic melts, such as metallic or ceramic melts, for example. Examples of metallic materials include alumin~~i~~um, magnesium, zinc, tin or even precious metals.

The process according to the ~~invention~~disclosure leads to weight reduction and strength increase in comparison to the corresponding compact articles.

"Pressure regulated" in the sense of the ~~invention~~disclosure means that in the course of the process the pressure exerted on the propellant is varied for metered addition of the propellant.

In this case the pressure exerted on the propellant during the propellant injection phase is greater than the pressure exerted on the propellant in the phases between or before or after metered addition. This means in the case of critical or compressible propellants, for example, that the pressure exerted in the intermediate cycle times is lower than the holding pressure of a pressure relief valve or overflow valve.

Therefore, according to the ~~invention~~disclosure, the required proportion of propellant is added to a melt to be foamed at a defined time over a defined period of time under a defined pressure.

The magnitude of the pressure exerted on the propellant during the metered addition is determined in particular in dependence on the required quantity of propellant, the type of article to be produced as well as the selected process parameters.

The present ~~invention~~disclosure is explained in more detail below with reference to the figures on the basis of a preferred embodiment by the example of the addition of a compressible fluid. It goes without saying that the following explanation may also be applied in principle to non-compressible fluids such as water, for example.

~~Figures 1a-1d~~

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing and other objects and advantages of the embodiments described herein will become apparent with reference to the following detailed description when taken in conjunction with the accompanying drawings in which:

FIGS. 1A-1D show the individual stages of the process according to the ~~invention~~disclosure for the production of physically foamed injection mo~~u~~lded articles;

~~Figure~~

FIG. 2 schematically shows a device for executing the process according to the ~~invention;~~

~~Figure~~disclosure;

FIG. 3 is a graph showing the pressure curve during execution of the process;

~~Figure~~ and

FIG. 4 shows a variant of ~~Figure~~FIG. 1 with direct introduction of the propellant into the cavity.

DETAILED DESCRIPTION OF THE DRAWINGS

As ~~Figure~~FIG. 1~~a~~A shows, the cavity 1 of any injection mo~~u~~lding plant is partially initially filled in a first stage firstly with a compact propellant-free melt 6. In this case, ~~the~~a feed pipe 3 for a compressed propellant is closed, for example, by a valve 4 such as a pressure relief valve 4 (overflow valve).

After the cavity 1 has been filled with a desired quantity of propellant-free melt 6, the feed pipe 3 for the propellant is opened and the propellant is injected in compressed, preferably liquid, state via the injection point 5. Through contact with the hot melt, the liquid propellant turns to gas and expands under the lower pressure in the cavity.

As a general rule the propellant is still liquid and not gaseous at the injection point 5 itself, and therefore one cannot talk of a "gasification point" in a narrower sense.

~~The~~

A mixture 7 of gaseous propellant and melt flows into the cavity 1 and causes the cavity 1 to fill completely, in which case the propellant-free melt portion 6 which was used for the initial filling comes to rest in the region of the cavity walls and forms the external skin or edge zone of the injection mo~~u~~lded article to be formed.

The cavity 1 can be ready filled as desired and required up to the maximum filling quantity with melt mixed with propellant or, as shown in ~~Figure~~FIG. 1~~d~~D, propellant-free melt can again be fed to the cavity in a third stage. In this case a foamed article is obtained which has a compact firm external skin right around which is formed by propellant-free melt.

After foaming and hardening, the finished injection mo~~u~~lded article, e.g. made of integral foam, is removed from the cavity and the cavity is immediately available again for the next charge.

As shown in ~~Figure~~FIG. 1~~d~~D, injection mo~~u~~lded articles, which have a cellular foamed internal core and a compact firm closed external skin, are obtained with the process according to the ~~invention~~disclosure.

Contrary to the known foaming processes, such as those described above, in which the cavity is filled completely with a melt/propellant mixture, according to the

~~invention~~disclosure an initial filling with propellant-free melt occurs firstly, as a result of which the formation of a uniform closed compact external skin is effected and articles with excellent surface characteristics can be obtained.

It is essential for execution of the process to prevent premature expansion of the propellant held under pressure. This can be achieved by appropriate insulation of the device and/or maintaining a suitable pressure level.

The metered addition of the propellant is conducted in a time- and pressure-controlled manner for the process according to the ~~invention~~disclosure. Control can be carried out via a device which is also the subject of the ~~invention~~disclosure.

As shown in ~~Figure~~FIG. 2, the propellant stored under pressure in a storage means 11, e.g. a pressure cylinder etc., is fed to a pressure control valve 10, which can be a multi-way valve such as a 3/3- or 2/3-way proportional valve, and should advantageously have a very quick reaction time and precise regulation.

During the propellant injection phase, i.e. the phase in which the propellant is added to the melt, in the case of critical propellants, the compressed propellant passes via a pressure relief valve 4 to the injection point 5 and there is added to the melt.

In this case, the dimensions of the pipes, connection pieces and also the parts of the technical control system of the process are such that no premature expansion in volume of the propellant under pressure is possible.

In the case of a sudden increase in volume the aggregate state of the agent can change, i.e. the agent changes into a gas, in which case vaporization cold is generated, which would in turn block the pipes as a result of "icing."

An increase in temperature on the way to the injection point 5 would also lead to a change in the aggregate state. For prevention, insulation of the heat-carrying elements is recommended.

In order to prevent premature expansion, all feed pipes should be as short as possible. Consequently, the pressure control valve 10 is preferably constructed to be as close as possible to the injection point 5. An improvement to the control characteristics of the control valve is also achieved as a result of the thus shortened feed pipe to the injection point 5.

If critical propellants are used, a pressure relief valve or overflow valve 4 is provided before the injection point 5, this valve ensuring that the pressure in the device does not drop below a specific value, preferably p (crit) at the given temperature, at which the transformation of the propellant into gas would take place. If, for example, carbon dioxide is used as propellant, a pressure of at least 60 bar should be maintained at room temperature in order to keep the carbon dioxide in the device upstream in liquid state.

The pressure relief valve 4 ensures that the propellant remains in compressed state even during outage times of the machine, e.g. in the intermediate cycle times before and after or between the propellant injection phases. A full release of pressure

only occurs when the machine or control system is switched off. Several pressure relief valves with "falling" pressure values may also be provided so that a pressure gradient is formed in front of the injection point 5 in the feed pipe section between the pressure control valve 10 and the pressure relief valve 4.

The graph in ~~Figure~~FIG. 3 schematically shows the pressure curve for executing the process according to the ~~invention~~disclosure using the example of compressible propellants.

Outside of the propellant injection phase, as in the intermediate cycle times, it is sufficient to keep the device at a selected pressure, at which the propellant respectively used remains in compressed, preferably liquid, state (section 20).

During the propellant injection phase (section 22), an elevated pressure is introduced in the feed pipes through the pressure control valve 10 so that the opening pressure (holding pressure) of the relief valve 4 is exceeded and the feed pipe section 3 up to the injection point 5 is quickly filled with liquid medium.

In this case, the pressure increase is proportional to the desired quantity of propellant to be fed to the melt. After time ~~t~~"t" expires, as soon as the desired quantity of propellant has been added to the melt, the pressure is reduced again to the starting pressure (section 24).

In ~~Figure~~FIG. 3, sections 21 and 23 show the pressure build up or reduction phase.

The injection point 5 is preferably configured as a throttle means, e.g. as a defined gap in an injector, a sintered metal injector, or a needle valve. According to the ~~invention~~disclosure, a controlled closure mechanism is located at the injection point. The quick pressure increase and the resistance through the injector prevent the propellant from transforming into gas, while the agent flows on from the pressure control valve 10.

The above measures ensure that the transformation of the agent into gas only occurs upon exit from the injector and when in contact with the hot melt, and that the inflowing melt is foamed.

The controlled closure mechanism can be omitted if a pressure relief valve is provided.

After the propellant injection phase has ended, i.e. after the desired quantity of propellant has been added to the melt, the pressure in the feed pipe to the injection point 5 is reduced so that no propellant can flow on. However, in the pipe up to the pressure relief valve 4 the starting pressure remains in order to keep the agent in compressed or liquid state for the next cycle. A virtually pressure-free and thus gaseous state prevails only in the short feed pipe section from the pressure relief valve 4 to the injection point 5 until the next cycle.

It goes without saying that this part of the plant may also be kept under pressure if required by the provision of a suitable closure mechanism which opens

again at the beginning of the propellant injection phase as a result of the increasing pressure level.

The pressure control via the pressure control valve can occur automatically by providing pressure measurement points 12, 13, for example, in front of and behind the pressure control valve.

If carbon dioxide is used as propellant, for example, the plant is preferably held at an operating pressure of at least 60 bar at room temperature, so that the CO_2 also remains in compressed state during the periods between the propellant injection phases. At the beginning of the propellant injection phase, a desired working pressure of about 200 bar, for example, is built up (section 21) in order to assure an adequate flow of propellant to the melt. After the propellant injection phase 22 has ended, the pressure is reduced again to the desired operating pressure.

The injection point 5 is preferably located in the feeder pipe 3 close to the spray point ~~x~~"x." According to a further embodiment, as is shown in ~~Figure~~FIG. 4, the propellant can be added directly to the melt in the cavity. In this case, the injection point 5 is located directly at the cavity.

In addition, the build up of a counterpressure can be provided in the cavity 1, such as is also used in conventional injection mo~~u~~lding processes in the so-called gas counterpressure process.

Very short cycle times can be obtained with the process according to the ~~invention~~disclosure. Hence, the process according to the ~~invention~~disclosure is also

very well suited to the production of mass-produced articles. The short cycle times are supported by the vapori~~s~~zation cold resulting upon the transformation of the propellant into gas, and this causes a reduction in the cooling time, and thus also the cycle time.

Should there still be propellant residues present in the pore structure in the core of the article after demo~~u~~lding, these slowly diffuse out of the article without detriment to its usability or recyclability.

Excellent dimensional stability of the article is achieved as a result of its closed firm external skin. In addition, foamed injection mo~~u~~lded articles which have a homogeneous uniform external skin and excellent tactility can be obtained with the process according to the ~~invention~~disclosure.

The foamed injection mo~~u~~lded articles obtained have an excellent surface quality and do not require any further finishing. It is also of advantage that the cavity does not need to be treated with a separating agent.

The process according to the ~~invention~~disclosure for the pressure-controlled metered addition of physical propellants to an expandable melt can be conducted advantageously with a device comprising a storage means 11, in which the propellant is stored under pressure, a pressure control valve 10 for regulating the propellant pressure and an injection point 5, which is preferably configured as a throttle means, at which the propellant under pressure is added to the melt, wherein the injection point 5 includes a controlled closure mechanism, and in the case of critical propellants at

least one pressure relief valve 4 is provided which is positioned downstream of the pressure control valve 10.

Although the above-described process and the device for the pressure-controlled metered addition of propellants under high pressure can be advantageously used for the production of physically foamed injection moulded articles, they are, of course, also suitable for other processes in which propellants are added under high pressure to melts to be expanded.

~~List of Reference Numbers~~

~~1 — cavity~~

~~2 — melt feed~~

~~3 — propellant feed pipe~~

~~4 — pressure relief valve~~

~~5 — injection point~~

~~6 — propellant-free melt~~

~~7 — melt with added propellant~~

~~8 — injection of plastic material~~

~~9 — mould comprising two halves~~

~~10 — pressure control valve~~

~~11 — propellant storage means~~

~~x — spray point~~

~~Section 20 — pressure during the intermediate cycle times~~

~~Section 21 — pressure build up phase~~

~~Section 22 — propellant injection phase~~

~~Section 23 — pressure reduction phase~~

~~Claims:~~

~~1. Process for the production of~~

What is claimed is:

PROCESS FOR THE PRODUCTION OF PHYSICALLY FOAMED INJECTION MOLDED ARTICLES

ABSTRACT

A process for producing physically foamed injection mo~~u~~lded articles~~,~~ ~~wherein in a first stage~~ is provided. The process involves feeding a propellant-free ~~first melt portion (6) is fed into a cavity (1) (initial filling), in a second stage~~thermoplastic melt into a cavity followed by delivering a physical propellant ~~is added at elevated pressure to the following melt portion (propellant injection phase), and possibly in a third stage a propellant-free further melt portion is charged~~directly into the cavity ~~(1), the production of the injection moulded articles occurring in the cavity,~~

~~characterised in that metering of the physical propellant in the second stage occurs in a pressure regulated manner, wherein the pressure which is~~or directly into the melt flowing into the cavity. The pressure exerted on the propellant during the ~~propellant~~ injection ~~phase~~stage is greater than ~~the pressure which is~~that exerted on the propellant ~~in the phases between or before or after metered addition, and the expansion of the propellant occurs in the cavity (1).~~

~~2. Process according to Claim 1, characterised in that the propellant is a compressible fluid.~~

~~3. Process according to Claim 1 or 2, characterised in that the propellant is kept under pressure in the intermediate cycle times before and after the propellant injection phase, or is present in a compressed state.~~

~~4. Process according to Claim 3, characterised in that in the intermediate cycle times the propellant is held a pressure of at least p (crit) of the propellant at the given temperature.~~

1

~~5. Process according to one of the preceding claims, characterised in that the pressure exerted on the propellant is controlled via a pressure control valve (10).~~

~~6. Process according to Claim 5, characterised in that the pressure control valve (10) is a multi-way valve.~~

~~7. Process according to Claim 6, characterised in that a 3/3-way proportional valve or a 2/3-way proportional valve is used as multi-way valve.~~

~~8. Process according to one of the preceding claims, characterised in that the pressure control in the case of critical propellants additionally occurs via at least one pressure relief valve (4) which is connected downstream of the pressure control valve (10).~~

~~9. Process according to Claim 8, characterised in that the holding pressure of at least one of the pressure relief valves (4) is equal to or higher than the pressure at which a critical propellant is held in the intermediate cycle times.~~

~~10. Process according to one of the preceding claims, characterised in that the pressure preset by the pressure control valve (10) is regulated via one or more pressure relief valves (4) to the injection pressure at which the propellant is added to the melt via an injection point (5).~~

~~11. Process according to one of the preceding claims, characterised in that the injection point (5) is configured as a throttle means.~~

~~12. Process according to Claim 11, characterised in that the injection point (5) is in the form of a defined gap in an injector or of an injector with a sinter metal.~~

~~13. Process according to one of Claims 11 or 12, characterised in that the injection point (5) is configured as a controlled closure mechanism.~~

~~14. Process according to Claim 1 or one of the preceding Claims 3 to 13, characterised in that water is used as propellant.~~

~~15. Process according to one of the preceding Claims 1 to 13, characterised in that a gas or gas mixture is used as propellant.~~

~~16. Process according to Claims 15, characterised in that carbon dioxide is used as propellant.~~

~~17. Process according to Claims 16, characterised in that the carbon dioxide is held in the intermediate cycle times at a pressure of at least 60 bar (= p (crit) CO_2 at room temperature).~~

~~18. Process according to one of the preceding claims, characterised in that for the propellant injection phase the propellant is brought to a pressure of over 60 bar via the pressure control valve (10).~~

~~19. Process according to one of the preceding claims, characterised in that a counterpressure is generated in the cavity (1).~~

~~20. Process according to one of the preceding claims,~~

~~characterised in that the physically foamed injection moulded article is selected from a handle, a knob, a gearshift knob, a steering wheel casing, a ball, a sphere, a fender, a float and a closing means for bottle-like containers.~~

~~21. Device for the metered addition of physical propellants to a foamable melt, wherein the device comprises a storage means (11), in which the propellant is stored under pressure, a pressure control valve (10) for regulating the propellant pressure, and an injection point (5), which is configured as a throttle means, at which the propellant under pressure is fed to the melt,~~
~~characterised in that a controlled closure mechanism is provided at the injection point (5).~~

~~22. Device for the metered addition of physical propellants according to Claim 21,characterised in that instead of the controlled closure mechanism or in addition to the controlled closure mechanism, at least one pressure relief valve (4) is provided.~~

during the holding phase.